

FIG. 2

FIG. 2A

Γ	-0-	
Date & Time	1 13:21 1 13:03 1 13:07 1 13:08	
Date 8	16:05:01 16:05:01 16:05:01 16:05:01	
Type	Microsoft Excel-Tab Microsoft Excel-Tab Microsoft Excel-Tab Microsoft Excel-Tab	
Size	550KB 550KB 550KB 550KB	
Name	☐ 1 ☐CBM.xls ☐CBM.Reports.xls ☐CBM.transfer.xls	
ᆀ		
☐ Desktop	☐ My Computer ☐ Diskette A ☐(C:) ☐(D:)	Data Deciding COBA Calculator COTA COCO COC

FG.3

Shift Schedule	A B C			Main	5	Ħ	H		¥	F	Σ	z	0	۵	Ø	œ	S	F	\supset
14 700	Shift Schodule				_ "										c H			F	
14			shift start				- Sun	\sim	l.,	suit	Shift	preak1	-		<u>اق</u> ق	preak2	break2	shift	all the
14	Vonday Tuesday Mednesday Linysday	4444	88888		0000	0000	<u>66666</u>	0000	i	<u> </u>	<u> </u>	<u> </u>	2 2 2 2 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	88888	22222 28888 88888	22222	8888	2888 88888	<u> </u>
1 1 1 1 1 1 1 1 1 1	Saturday Sunday Sunday	444	388	388	355	322	366 366 366	388	388	388	388	<u> </u>	<u> </u>	888 388	222 288 888	222	222	222 222	888 888
23.00 185.00 186.000 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 186.000 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 186.000 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 186.000 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 187.000 1 14.00 1 14.00 1 14.00 1 14.00 1 14.00 1 14.00 1 18.00 1 18.30 1 18.30 1 18.30 1 22.00 22.00 22.00	nitial Offset nitial Offset Only Lunch break applies Steaks apply for machines Neeks per year Pays off per year	>co≅	not working																
Second Start Sta	lours per day fours per dal/average lours per week lours per week/average lours per year	2.5.8.2.8. 8.5.8.9.9. 8.5.8.9.9.9.9.9.9.9.9.9.9.9.9.9.9.9.9.9.	-	7	က	4	ıol				6	10	=	12	55	4	55	19	17
8:00 8:15 10:00 10:30 14:00 16:00 16:15 18:00 18:30 22:00		==-	shift start	start br	_		- 1			endit			break1 end	start	_		break2 end	shift	start
8:00 8:15 10:00 10:30 14:00 14:00 16:00 16:15 18:00 18:30 22:00																			
			00:9	8:00	- 1		10:30		_	14:00	14:00	16:00	16:15	18:00	18:30			-	22:00

FIG. 4

3:00 3:15 7:00 3:00 3:15 7:00 3:00 3:15 7:00	_
3:15	
H	
	-
R 3000	
21:00 0:30 21:00	
20:00 20:00 20:00	
0 3:15	
N 00:0:	
15:00 15:00 15:00	
15:00 15:00 15:00	
X 5:15	
15:00	
- 65 55 5 - 60 50 5 - 60 5 -	
12:00 12:00 15:00	
8:15	
800.8	
2.00 2.00 2.00 2.00 2.00	
0 25245575860220	នេ
H	
ပ	
<u> </u>	당

FIG. 4A

Q V					_	
Н					_	
¥			break	222222 222222	00:0	
AM		13		222222 2222222	000	
AL.		shift 3	Innch	<u> </u>	00:2	
¥			total	222222 2222222	26:00	
A					_	
A		2		222222 222222	00:0	
AH		shift	_	<u> </u>	7:00	
AG			total	2000 C	00:99	
AF			break2	2888888	00:0	
ΑĒ		_	break1 b	5555555 55555555	0:00	
AD		shift	lunch	555555	7:00	ŧ
AC			total	<u> </u>	24:00 24:00 24:00	Default
AB			a suff	222222	22 Tilling	↑
AA			break 2 end	322222	23 break 2	
7		က	break 2 start	3888888	22 bpeak 2 t	
>		SHI	Gud euch	3888888	21 Euroh band	230
×		ক	unch	555555 555555	20 Starth	
×			break 1	5555555 XXXXXXX	1	1 1
>			start	2888888 88888888	1 -	1
\vdash	-	7	3	 		2
_		•				

FIG. 4B

AJ AK AL AM AN AO								
F								
¥								
8								
AF AG AH A								
¥								
¥								
AE								
AC AD AE	7:00 → Customer 1	7:00 → Customer 3	✓ Customer 4					
AB	7:00	7:00						
AA								
Z								
-	2:00	5:00						
×	4:00 5:00	4:00						
3								
>								
	31	336	35	36	38	8	\$14	42

FIG. 4C

$\overline{}$		15 2	_	
S		maintenar qu	MTBM 4080 4080	
Н		mair	≥	
<u>~</u>	- 1	_	M oo	
 -	1	month		
Ø	- 1	=	MTBM 680 680	
Н	-	+	<u>×</u>	
a.	- 1		offset 0 0	
H	- 1	grafic		
0	ı		׺ºº	
Н		=	œ	
		h/mir 1	MTTR 0	
H		failure (h/min) level 1	<u></u>	
<u> </u>	Ш	faii	MTBF	
L Main			_	
		~*	MTT 0	
		maintenance (h/min) shift	ATBM 163.2 163.2	
ي پ) (e	MTBM 163.2 163.2	
Database		euar	MTTR 0	
☐ gat ☐		iii iii	Σ	
		- P	MTBA 0	
		2	MTR -	
H # I		im (ii	1 —	
G 1 F	Ш	assists(min/ min)	MTBA 80 80	
H^-	╽╢			
-	98	transport system S/D. synch	o -	
$H \cup I$	ig.	Short		
la fe	l m	Solar	- o E	
I E	Return to the Main page			
	훈	# of process	8 00	
	"	ΤŤ	П	
11 -				
.₫				
<u>a</u>				
B			8	
"=		11	ورا	
Line Configuration		4	7300 Buffer	3
<u></u>			1300	
甘		row row delete row		
			- 0	
Ц		M ω 4	ကတင္	

FIG. 5

AG		
AF		
	stion stion	
AE	Initial Position B1 conv5_2001	
	Dual	
AD	Witness Module Dual Lane 0 Con 2.2	
AC	Witness Module Single Lane Buffers Corn/2_1	
AB		
AA	grafic length offset 0 0 0	
Z		
F	F MITH MIBE MID	
F	(h /m/ 1) e (l /m/ 1)	
×	O O W I I I I I I I I I I I I I I I I I	
≥		l
	Wei Buo	
F		
2	M MBM W 1001 10018 (u	l
-	43883888888888888888888888888888888888	
-		1

FIG. 5A

	FIG. 5B
AU AV AW AX AY AZ	Bare Board Loader Buffer Conveyor 1506 Conve
	-0~4~ <u>00110110100000000000000000000000000</u>




FIG. 5C

Delete Database Main	Miles Mile
Insert Return to the Main page	# 0
Line Configuration	Sin Printer Sin Printer
∀	(1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -

FIG. 6

0 P Q R		m	TTM MTBM MTTM	163.20 16		
z Z			R MTBM			
H - H		failure (h / min)	Ievel 1 level 2 level 2 with mide mit			
P. G			ASSISTS (min / min) MTBF MTTR IN			88888
D						
0	Line				-0	
В		0000	7956	-4644667895	 7580	1757 1753 1750 1750 1750 1750
A		Datahasa	Dalar		Bare Board Loader Buffer	Conveyor 1060 Conveyor 1590 Conveyor 2380 Conveyor 530

FIG. 7

_	
œ	888 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8
O	
۵	55 25 25 25 25 25 25 25 25 25 25 25 25 2
6	
F	
z	
Σ	ARCH R 84 8 8 5 5 5 5 5 8 8 8 8 8 8 8 8 8 8 8
\times	
F	
F	
F	
ß	
Ľ	සිසිසිසි සිසිසිසිසිසිසිසිසිසිසිසිසිසිසි
ш	<u>~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~</u>
	UW-UW0U4@0000000
Γ	
0	
Ĺ	44888888888888888888888888888888888888
<u></u>	105050 10
	SPL SPL SPL atton 180 x 2/SPL x 3/SPL
	00000000000000000000000000000000000000
A	SSPL SSPL ston 180 SSPL x 2SPL x 3SPL
	4.32R-L 4.32R-L 5.22R-L 5.02.23R-L 5.02.23R-L 5.02.23R-L 2.22.28R-L 5.02.23R-L 2.23.28R-R 2.23.28R-R 2.2
	Co
	77555555000000000000000000000000000000
Ш	84000000000000000000000000000000000000

FIG. 7A

L 8888		2000000 200000000000000000000000000000	88888	88888		888	8000	680.00
Q 	888888	<u> చరి</u>	333333	ಪಹಹಹವ. -	వ వవవవన	333	8888	386
1-1								
™	888888	3888888	322222	388888 222222	38888 22222	388	3888	63.2(
Д								
z								
Σ								
\exists								
7								
_								
크								
<u> </u>								
- 8888	33333	ඉ ඉඉඉඉඉ	සිසිසිසිසි	3222	3888	8888	88	
ш								
ш ∽∞−-сл	w001400	00000	0			-00	00	
_								
		200	-0000			-00+		
J		200				-00+		
ଧ୍ୟତ୍ରଧ	ಬರ್ಲಿ	9000o-	-m4-c	1-004 to	9000	000	20	
	58555	760000			88222	1221	31.5	
			_ contra					
		8085 8	igazino Sinoader MU05 rinter pro-flow rinter pro-flow temp control rinter squegee operation rinter squegee operation	-		lane		
		MB57 MB57 MC MC MC MC MC MC MC MC MC MC MC MC MC	der M emp c			24-0	<u> </u>	
ر برا [*]	_e kk	ast Lift Ragazine Buffer MB Ragazine Buffer MB Ragazine Loader M Ragazine Loader M	Agazine Unloader MU05 Angazine Unloader MU05 Antier pro-flow temp conti	<u> </u>		ttle - 1 lane to	TS L	
2/SPL 3/SPL 2/SPL	x2/ x3/	ine E	T pro-	, -0-0-0-	-0	9-2	attio	
74 × 2 / 2 / 2 / 2 / 2 / 2 / 2 / 2 / 2 / 2	F5 x 3 / SPL Flip Station 180 HS-50 HS-50 x 2 / SPL HS-50 x 3 / SPL	Last Lift Magazine Buffer MI Magazine Loader M Magazine Loader M Magazine Loader M	Magazi Printer Printer	28888 2888 28888 2888 28888 28888 28888 28888 28888 28888 28888 28888 28888 28888 28	25.25 25.25 27 27		Turn Stat	
8888	<u> 1</u>	<u> </u>	800000	282582		, 5,557		ım

FIG. 7B

_																																														
æ		860	00000	3	68000	000	000.00	680 00	3	68000	0000	000.00	680 00	0000	0000	68000	0000	000.00	680 00	0000	0000	680.00	00000	000.00	680 00	00.00	999	680.00	0000	900.00	680.00	680 00	000		0000	980.00	680 00	0000	980.00	680.00	680 00	0.00	90.08	680 00	0000	000,00
ø	1																																													
۵		163.20	469 00	20.50	163.20	10000	103.20	163.20	200	163.20	0000	100.20	163.20	0000	03,20	163 20	0000	02:00	163 20	162 20	250	163.20	40000	02:20	163.20	200	163.20	163.20	000	103:20	163.20	163 20	000	35	00.50	163.20	163 20	0000	02:20	163.20	163.20	3	163.20	163.20	16000	103.20
0	,																																													
z	1																																													
Σ																																														
¥																																														
	1																																													
H																																														
5																																														
H																																														
F																																														
Ш																																														
۵																																														
0																																														
В																																														
A																																														
	00	69	102	1		1	7/	73	li	74	75	2	761	11		78		2	-08	1	ā	85	S	র	84	- 1	S	92	ī	7	88	68	5	5	1	35	63	Iz	94	35	18	য়	37	80	श	38

FIG. 70

												_							_		
AH																					
AG																					
AF																					
																200	<u>\$</u>	5	35	88	500
AE																					
AD		inbound routing														Printermo	con5 2001	con5_2001	con5_2001	con5_2001	Conveyor001
AC	witness	module dual lane	TO COMPANY THE PARTY OF THE PAR																	Conv5_2	
AB	witness	module single lane														BareBoard_Loader				Conve	١
Z AA	grafic	high level length offset																•		-	
>	grafic	detailed length offset	o	00	0	0	-	00	00	0	00	0	00	00	000	00	0	0 0	> <	0	0
×	gu	det														520	<u>당</u>	윦	25	38	500
8		MTTM																			
^		MTBM N	18160.00	8160.00	8160.00	8160.00	8160.00 8160.00	8160.00	8160.00	8160.00	8160 8160 8160 8160 8160 8160 8160 8160	8160.00	8160.00	8160.00	8160.00 8160.00	8460.00	8160.00	8160.00	8160.00	8460	8160.00
D		terly MTTM																			
H		A MTBM MTT	080.00	4080.00	00000	800	98	000	800	080.00	000	080.00	080	888	4080.00	980.00	08000	080.00	080.00	0000	080.00
S	e(h/min)	thly MTTM	4	44	4	4.	4 4	44	1 4	4	44	. 4	4-5	14	444	44	+ 4	4	4.	44	4
П	 2	_	2	9	- 00	0	2=	24	ώ <u>4</u>	12	10	18	96	315	222	120	210	8	62	346	32

FIG. 7D

_	
АН	
Н	
AG	
H	
AF	
L	84,50 84,50 87,50
	4%24
AE	
	00 00 00 00 00 00 00 00 00 00 00 00 00
ΑD	LITH ILITH I
L	
	SSSSCALEGE SSSSCALEGE SSSSSCALEGE SSSSSCALEGE SSSSSCALEGE SSSSSCALEGE SSSSSCALEGE SSSSSCALEGE SSSSSCALEGE SSSSCALEGE SSSSCALEGE SSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSS
AC	SSECTURENT SSECTIVENT
H	
AB	### SECONARION 1 155
^	Signification 15 (1985) Signification 15 (1985) Signification 16 (1986) Signif
¥	3350000 TTTTBBB2222 EEEE COOCOO0000000000000000000000000000
7	
F	000000000000000000000000000000000000000
ŕ	000000000000000000000000000000000000000
ľ	88888888888888888888888888888888888888
≥	
F	
þ	
F	40000000000000000000000000000000000000
H	
S	
	839898888888888888888888888888888888888

FIG. 7E

¥	
Н	
ΑG	
Н	
ΑF	
Н	
AE	
Н	
Α	
Н	
AC	
Ц	
П	
AB	
AA	
Z	
>	
×	
8	
>	4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4
b	
F	00000000000000000000000000000000000000
s	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
\vdash	<u> </u>
ட	Inital single in the property of the property

FIG. 7F




FIG. 8

_	21											666	999
													_
×	50											666	666
≥	6											666	66
_												6	6
>	18											666	66
_												666	66
>	17											6	6
_												666	66
-	16											0,	0,
-												666	666
S	15												
												666	666
œ	14												
_												666	666
ø	13												
												666	66
۵.	15												
												666	66
0	F												
												66	666
Z	유												
	 2	က	4	S	9	7	œ	တ	10	1	12	13	14

FIG. 8A

AN	30							666 666	
-									
AG	59							666	
_									
AF	28							666 666	
AE	22							666	
_									
AD	56							666 666	
AC	22							666	
							į		
AD	24							888	
_									
A	ន							88	
_									
7	83							666 666	
	 2	ω 4	S G	<u></u>	ထတ	 <u> </u>	2	ω 4	

FIG. 8B




FIG. 9




FIG. 9A




FIG. 9B




FIG. 10




FIG. 11




FIG. 12




FIG. 13

L	A	В	ပ	٥	E	ш	g	I	_
_	Maintenance		minutes	minutes # of workers	who does maint.	downtime factor	line operator (h)	maint. team (h)	downtime (h)
ς,	line workers								
.თ ∠	3 maintenance per shift (min)				-	100%	0.00	0.00	#DIV/0i
S	5 maintenance monthly add. (min)				- 0	% 0 0 0 0 0 0	0/XIC#	# 	0/AIC#
9	maintenance quarterly add (min)				1 co	100%		0.00	i0/AIQ#
^	maintenance every x h add (min)	10,000			က	100%	0.00	0.00	#DIV/0i
∞σ	maintenance time calculated (h)						100XI Q ##	10/NG#	i0/NIQ#
9									
	11 maintenance costs per year							#DIV/0i	0.000000€
12									
13									
4 4									
9									
1									
18									
19							ſ		
ଧ						Main			
7 6							7		
7									

FIG. 14

¥		aar 0.00 #DIV/0! #DIV/0! #DIV/0!	83.56 #DIV/0! #DIV/0! #DIV/0!				
ſ	Capacity	hours available per year internal setup #L maintenance #E quality technical availability hours total #E hours total #E	boards per hour boards per shift boards per week boards per year			Main	
	١			l			
н	%	##### 0	##### 0	##### 0	####	####	
ш	ard	0	0	0	0	0	0
F	Cost per board	#DIV/0i	#DIV/0i	#DIV/0!	#DIV/0i	#DIV/0i	#DIV/0i
Ε		0000	000	000	00000	000	0
D	Cost per year	0000	#DIV/0! 0	i0/AIQ# 0/AIQ#	0 10//\lQ# 10//\lQ# 10//\lQ#	#DIV/0! #DIV/0! #DIV/0!	#DIV/0i
B C	a	%%			sqm kw cbm/h NI/min		
А	Cost of Ownership	Investment	8 Labor 9 Operations 10 Supervisor 11	13 Misc. 14 Setup 16 Maintenance 17	18 Utilities 19 Floorspace 21 Electricity 22 Nitrogen 24 Nir	25 Quality 26 rework costs per year 27 scrap costs per year 28 22	Costs per vear

FIG. 15




FIG. 16





FIG. 16A







FIG. 18






FIG. 20





FIG. 21






FIG. 23









FIG. 24














FIG. 30




FIG. 31





FIG. 32






FIG. 34




FIG. 35




FIG. 36